

# GUARDIQUE

## REFERENCE SELF LL04

**DESCRIPTION** Double-sided adhesive tape

**ADHESIVE** **Type** Modified acrylic

**LINER** **Type** Siliconized paper  
**Weight** 80 grs/sqm  
**Colour** Havana

**CARRIER** **Type** Multidirectional polyester mesh (rectangular)

### PHYSICAL PROPERTIES

<b>ADHESIVE STRENGTH AFERA 5001 (N/25 mm):</b>	<b>28</b>	<b>+3</b>
<b>COHESION FINAT-8 (nr hours: 1kg/6,25cm2):</b>	<b>Min. 2,5</b>	
<b>THICKNESS (mm without liner):</b>	<b>0,09</b>	<b>+7%</b>
<b>TEMPERATURE RESISTANCE (°C):</b>	<b>-30/+100</b>	

### APPLICATIONS

Lamination of materials requiring not longitudinal or transversal stretch. Application on porous materials. Specially recommended for polyurethane

#### Shelf life and storage instructions

12 months from Guardique delivery time when stored in original boxes at temperature of 21°C and a relative humidity of 50%.

The quality and durability of the tape may vary according to temperature and humidity. Low temperatures can increase the risk of condensation, consequently reducing the tack of the self-adhesive product

#### General points

Guardique recommends paying special attention to contact surfaces, checking that they are totally clear of grease, oil, dust or any other non-stick substance.

The technical data shown in this document are for the final user's guidance and therefore they do not constitute a legal warranty in relation to certain properties caused by numerous influences that may act during handling and use of our products.

Prior to use, purchasers should determine the suitability of this product for the specific purposes and assume all risk and liability in connection with them